



SPECIALTY UV CLEAR



Construction

Ply	2
Mil Thickness	2

Performance Specifications	Glass Type 1/4"	1/8"
Solar Energy Transmitted %	78	81
Solar Energy Absorbed %	16	13
Solar Energy Reflected %	6	6
Visible Light Transmitted %	87	89
Visible Light Reflected % - Interior	6	6
Visible Light Reflected % - Exterior	7	6
Ultraviolet Rejected %	99	99
Shading Coefficient	.95	.98
Solar Heat Reduction %	5	2
Total Solar Energy Rejected %	17	15
Glare Reduction %	3	1
Emissivity	.86	.86
U-Value	1.12	1.15



Film-To-Glass Installation Ratings Specialty UV Clear

Single Clear	1
Dual Clear	1
Single Tinted	1
Dual Tinted	1
Low-E	1

Film-To-Glass Installation Ratings

- 1** = Approved for TSF & IGU Seal Failure warranty coverage at no additional fee.
- 2** = NOT approved for TSF & IGU Seal Failure warranty coverage. Apply for coverage with fee.
- 3** = TSF & IGU Seal Failure warranty coverage is NOT available.

Important

Data created from testing of film installed on 1/8" and 1/4" thick clear float glass. Data is representative of actual production. Batch to batch variations are within industry standards.