



**GLOBAL**<sup>®</sup>  
Window Films

*Driven by Quality!*

Premium  
Automotive  
Window Films



## About Global

Global automotive window films are designed to meet the demanding expectations of finicky installers and their high-end customers. With their great looks and strong manufacturer backed warranties, Global is the ideal choice to build your business and your reputation.

There are 4 series of Global automotive window films:

- |                        |                      |
|------------------------|----------------------|
| 1) QDP Ceramic         | 3) NR Quick Dry Plus |
| 2) HP Charcoal Premium | 4) NR Quick Dry      |

## Global Service Centers

### **Express Window Films**

East Coast Service Center  
22 Shelter Rock Lane - #106  
Danbury Connecticut 06810

### **Express Window Films**

West Coast Service Center  
1055 South Melrose Avenue - Unit A  
Placentia California 92870

### **Express Window Films**

Southeast Service Center  
1587-C College Park Business Center Road  
Orlando Florida 32804

**Direct** 203.798.2211

**Toll Free** 800.FILM NOW (800.345.6669)

**Fax** 203.798.2253

**Email** support@filmnow.com

***www.filmnow.com***



## QDP Ceramic (86, 80, 70)

### Description

The ultimate automotive window film from Global has it all: great looks, signal-friendly performance and the protection of a lifetime color-stable warranty. This premium 2-ply, 2-mil film is ideal for the top slot in your customer offerings. QDP Ceramic will take your business and your profits to new heights.

### Snapshot

Name	QDP Ceramic
Category	Automotive
Series	Ceramic
VLT Options - 3	86, 80, 70
Ply	2 Ply
Thickness	2.0 Mil
Metal	Metal Free
Color	Dye Free
Polyester	Weatherable
Liner	Polyester
Adhesive	Pressure Adhesive
Scratch Resistant	Yes
Warranty	Lifetime
Color Stable	Yes

QDP Ceramic (86,80,70)



## QDP Ceramic 86

Category	Automotive
Series	Ceramic
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	2.0 Mil
Metal	Metal Free
Color	Dye Free
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	86%
GR	Glare Reduction	6%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	9%
TSER	Total Solar Energy Rejected	27%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## QDP Ceramic 80

Category	Automotive
Series	Ceramic
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	2.0 Mil
Metal	Metal Free
Color	Dye Free
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	78%
GR	Glare Reduction	14%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	9%
TSER	Total Solar Energy Rejected	42%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## QDP Ceramic 70

Category	Automotive
Series	Ceramic
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	2.0 Mil
Metal	Metal Free
Color	Dye Free
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	70%
GR	Glare Reduction	30%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	8%
TSER	Total Solar Energy Rejected	49%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## QDP Ceramic

### Description

The ultimate automotive window film from Global has it all: great looks, signal-friendly performance and the protection of a lifetime color-stable warranty. This premium 2-ply, 2-mil film is ideal for the top slot in your customer offerings. QDP Ceramic will take your business and your profits to new heights.

### Snapshot

Name	QDP Ceramic
Category	Automotive
Series	Ceramic
VLT Options - 7	50, 46, 42, 38, 33, 18, 05
Ply	2 Ply
Thickness	2.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Polyester	Weatherable
Liner	Polyester
Adhesive	Pressure Adhesive
Scratch Resistant	Yes
Warranty	Lifetime
Color Stable	Yes

QDP Ceramic



## QDP Ceramic 50

Category	Automotive
Series	Ceramic
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	2.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	51%
GR	Glare Reduction	44%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	7%
TSER	Total Solar Energy Rejected	51%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*

**QDP Ceramic 50**





## QDP Ceramic 46

Category	Automotive
Series	Ceramic
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	2.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	46%
GR	Glare Reduction	54%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	7%
TSER	Total Solar Energy Rejected	52%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## QDP Ceramic 42

Category	Automotive
Series	Ceramic
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	2.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	42%
GR	Glare Reduction	54%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	7%
TSER	Total Solar Energy Rejected	53%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## QDP Ceramic 38

Category	Automotive
Series	Ceramic
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	2.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	38%
GR	Glare Reduction	58%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	7%
TSER	Total Solar Energy Rejected	56%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



### QDP Ceramic 33

Category	Automotive
Series	Ceramic
Warranty	Lifetime Color Stable

#### Construction:

Ply	2 Ply
Thickness	2.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

#### Performance:

VLT	Visible Light Transmission	32%
GR	Glare Reduction	65%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	7%
TSER	Total Solar Energy Rejected	58%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## QDP Ceramic 18

Category	Automotive
Series	Ceramic
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	2.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	18%
GR	Glare Reduction	82%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	6%
TSER	Total Solar Energy Rejected	65%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## QDP Ceramic 05

Category	Automotive
Series	Ceramic
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	2.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	4%
GR	Glare Reduction	96%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	6%
TSER	Total Solar Energy Rejected	66%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## HP Charcoal Premium

### Description

The perfect match! Your customers will love how great HP Charcoal Premium looks, and you'll love how easy it is to install. This metal/dye hybrid film has a beautiful charcoal tone that's ideal for matching to most factory tinted glass. And, on top of great looks and easy handling, the vapor deposition construction provides fast dry-out and little to no signal interference.

### Snapshot

Name	HP Charcoal Premium
Category	Automotive
Series	High Performance
VLT Options - 7	50, 45, 40, 30, 20, 10, 05
Ply	2 Ply
Thickness	1.5 Mil
Metal	Vapor Deposition
Color	Deep Dip Traditional Dyed
Polyester	Weatherable
Liner	Polyester
Adhesive	Pressure Adhesive
Scratch Resistant	Yes
Warranty	Lifetime
Color Stable	Yes

HP Charcoal Premium



## HP Charcoal Premium 50

Category	Automotive
Series	High Performance
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Vapor Deposition
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	54%
GR	Glare Reduction	41%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	7%
TSER	Total Solar Energy Rejected	36%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*





## HP Charcoal Premium 45

Category	Automotive
Series	High Performance
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Vapor Deposition
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	44%
GR	Glare Reduction	52%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	7%
TSER	Total Solar Energy Rejected	40%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## HP Charcoal Premium 40

Category	Automotive
Series	High Performance
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Vapor Deposition
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	39%
GR	Glare Reduction	57%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	6%
TSER	Total Solar Energy Rejected	42%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## HP Charcoal Premium 30

Category	Automotive
Series	High Performance
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Vapor Deposition
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	28%
GR	Glare Reduction	69%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	4%
TSER	Total Solar Energy Rejected	43%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## HP Charcoal Premium 20

Category	Automotive
Series	High Performance
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Vapor Deposition
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	20%
GR	Glare Reduction	78%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	5%
TSER	Total Solar Energy Rejected	52%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## HP Charcoal Premium 10

Category	Automotive
Series	High Performance
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Vapor Deposition
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	10%
GR	Glare Reduction	89%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	4%
TSER	Total Solar Energy Rejected	54%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## HP Charcoal Premium 05

Category	Automotive
Series	High Performance
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Vapor Deposition
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	5%
GR	Glare Reduction	95%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	5%
TSER	Total Solar Energy Rejected	61%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## NR Quick Dry Plus

### Description

More than just a pretty face! Yes, NR Quick Dry Plus is possibly the best-looking auto film on the market today. But that's just the beginning of its appeal. This 2-ply, 1.5 mil workhorse of a film is color stable, metal-free and ultra-durable to keep its great appearance year after year.

### Snapshot

Name	NR Quick Dry Plus
Category	Automotive
Series	Non Reflective
VLT Options - 8	55, 50, 40, 35, 30, 20, 15, 05
Ply	2 Ply
Thickness	1.5 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Polyester	Weatherable
Liner	Polyester
Adhesive	Pressure Adhesive
Scratch Resistant	Yes
Warranty	Lifetime
Color Stable	Yes

NR Quick Dry Plus



## NR Quick Dry Plus 55

Category	Automotive
Series	Non Reflective
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	55%
GR	Glare Reduction	40%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	5%
TSER	Total Solar Energy Rejected	29%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*





## NR Quick Dry Plus 50

Category	Automotive
Series	Non Reflective
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	48%
GR	Glare Reduction	47%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	4%
TSER	Total Solar Energy Rejected	31%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## NR Quick Dry Plus 40

Category	Automotive
Series	Non Reflective
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	39%
GR	Glare Reduction	57%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	4%
TSER	Total Solar Energy Rejected	35%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## NR Quick Dry Plus 35

Category	Automotive
Series	Non Reflective
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	35%
GR	Glare Reduction	62%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	4%
TSER	Total Solar Energy Rejected	34%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## NR Quick Dry Plus 30

Category	Automotive
Series	Non Reflective
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	30%
GR	Glare Reduction	67%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	4%
TSER	Total Solar Energy Rejected	35%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## NR Quick Dry Plus 20

Category	Automotive
Series	Non Reflective
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	19%
GR	Glare Reduction	79%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	3%
TSER	Total Solar Energy Rejected	40%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## NR Quick Dry Plus 15

Category	Automotive
Series	Non Reflective
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	15%
GR	Glare Reduction	84%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	5%
TSER	Total Solar Energy Rejected	43%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## NR Quick Dry Plus 05

Category	Automotive
Series	Non Reflective
Warranty	Lifetime Color Stable

### Construction:

Ply	2 Ply
Thickness	1.5 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	4%
GR	Glare Reduction	96%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	3%
TSER	Total Solar Energy Rejected	44%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## NR Quick Dry

### Description

This is a 1-ply, 1-mil version of our NR Quick Dry Plus. NR Quick Dry is designed specifically for dealers who prefer a thinner NR film for installation speed.

### Snapshot

Name	NR Quick Dry
Category	Automotive
Series	Non Reflective
VLT Options - 6	70, 50, 40, 30, 20, 05
Ply	1 Ply
Thickness	1.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Polyester	Weatherable
Liner	Polyester
Adhesive	Pressure Adhesive
Scratch Resistant	Yes
Warranty	3 Year
Color Stable	No

NR Quick Dry





## NR Quick Dry 70

Category	Automotive
Series	Non Reflective
Warranty	3 Year

### Construction:

Ply	1 Ply
Thickness	1.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	72%
GR	Glare Reduction	21%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	7%
TSER	Total Solar Energy Rejected	26%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## NR Quick Dry 50

Category	Automotive
Series	Non Reflective
Warranty	3 Year

### Construction:

Ply	1 Ply
Thickness	1.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	52%
GR	Glare Reduction	43%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	7%
TSER	Total Solar Energy Rejected	30%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## NR Quick Dry 40

Category	Automotive
Series	Non Reflective
Warranty	3 Year

### Construction:

Ply	1 Ply
Thickness	1.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	38%
GR	Glare Reduction	58%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	6%
TSER	Total Solar Energy Rejected	35%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



### **NR Quick Dry 30**

Category	Automotive
Series	Non Reflective
Warranty	3 Year

#### **Construction:**

Ply	1 Ply
Thickness	1.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

#### **Performance:**

VLT	Visible Light Transmission	30%
GR	Glare Reduction	67%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	7%
TSER	Total Solar Energy Rejected	38%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## NR Quick Dry 20

Category	Automotive
Series	Non Reflective
Warranty	3 Year

### Construction:

Ply	1 Ply
Thickness	1.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	21%
GR	Glare Reduction	77%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	6%
TSER	Total Solar Energy Rejected	40%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



## NR Quick Dry 05

Category	Automotive
Series	Non Reflective
Warranty	3 Year

### Construction:

Ply	1 Ply
Thickness	1.0 Mil
Metal	Metal Free
Color	Deep Dip Traditional Dyed
Adhesive	Pressure Adhesive

### Performance:

VLT	Visible Light Transmission	6%
GR	Glare Reduction	93%
UVR	Ultraviolet Rejected	>99%
VLR-E	Visible Light Reflectance Exterior	6%
TSER	Total Solar Energy Rejected	41%

*Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.*



Distributed & Serviced by



## Global Service Centers

**Express Window Films**  
East Coast Service Center  
22 Shelter Rock Lane - #106  
Danbury Connecticut 06810

**Express Window Films**  
West Coast Service Center  
1055 South Melrose Avenue - Unit A  
Placentia California 92870

**Express Window Films**  
Southeast Service Center  
1587-C College Park Business Center Road  
Orlando Florida 32804

**Direct** 203.798.2211  
**Toll Free** 800.FILM NOW (800.345.6669)  
**Fax** 203.798.2253  
**Email** support@filmnow.com

***[www.filmnow.com](http://www.filmnow.com)***